
IK KESSEL

Controlfix clean out DN 150, Floor slab, black





Article information

Item no.: 80150S GTIN: 4026092004098 Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Fast, simple and toolless maintenance
- Quick and toolless access for cleaning

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

| General characteristics | black |
|---|--|
| Colour: | 150 |
| Nominal size (DN): | 160mm |
| Outer diameter (OD): | for wastewater with and without sewage |
| Type of wastewater: | floor slab installation |
| Installation situation: | Installation-ready (connection parts must be |
| Delivery state: | connected on site) |
| Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section: | 14 kg 17,32 kg 3000 mm |
| Cutout dimension, width: | 750 mm |
| Cutout dimension, length: | 750 mm |
| Vertical drop between inlet and outlet: | 9 mm |
| Installation depth: | 516 - 669 mm |
| Vertical adjustment: | vertically adjustable upper section |
| Length: | 486 mm |



Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Cover locking: Load class: Tightness: 590 mm length width height

including spigot and socket

Cover plate Polymer black 366 mm 366 mm Lock & Lift L 15 (EN 1253-1) surface water resistant